Mid Rise Lift XS35N

Performance and Productivity



Features


- 3500 kg capacity;
- The ideal lift for servicing tires, brakes, suspension and bodywork;
- Electro-hydraulic operation, high loading capacity and elevated lifting height, rapid cycle times, maximum safety to users;
- Practical and easy to use, convenient to move with optional portable kit.



Mid Rise Lift XS35N



SPECIFICATIONS	
Model	XS35N
Capacity	3500 kg
Overall Length	2160 mm
Overall Width	1950 mm
Drive-on Height	105 mm
Platform Length	1500 mm - 2160 mm
Platform Width	630 mm
Interval	690 mm
Stroke	950 mm
Lifting Time	20 s
Lowering Time	20 s







Rotary Lift


2700 Lanier Drive Madison, IN 47250, USA www.rotarylift.com


Rotary Lift Asia

No.1388,East Xiushan Road,Haimen, Jiangsu Province,China,226100 www.vsg-asia.com

Contact Information

Australia/New Zealand: 86.21.60812756 East Asia: 86.513.82263361 South East Asia: 91.80.41123421-26 India: 91.120.4099.555





105 mm minimum height suitable for a wide range of vehicles with low chassis.



Independent hydraulic twin cylinder system eliminates the need for mechanical locks and compressed air while offering increased flexibility with vehicle work height.



3 Slim control box is convenient to move and saves space, control panel is easy to operate.



4 Low limit switch prevents the lift from damage and ensures safety.



5 A set of four rubber adaptor pads are used for vehicle contact



6 Optional high strength cross bars can help serve a wider range of vehicles with short track widths.



Optional mobility kit offers convenient movement at work.