

# Vehicle Hoists

## STF40 - 4000 KG STANDARD 4 POST HOIST

Configured with added length and extra width the STF40 is ideal for the quick lifting and service of a wide range of vehicles. With jacking bridges available, this hoist is ideal for general mechanical servicing.

- 4000 kg lift capacity
- Extra wide between the columns
- Lift height of 1962 mm
- Manually operated safety locks
- Tilt ramps with non-skid coating
- Hammer tone powder coat finish



SPECIFICATIONS	STF40	STF40A
Max. Lift Capacity	4000 kg	4000 kg
Overall Length	5850 mm	5850mm
Overall Width	3276 mm	3276 mm
Overall Height	2221 mm	2221 mm
Width Between Posts	2718 mm	2718 mm
Length Between Posts	4701 mm	4701 mm
Platform Width	508 mm	508 mm
Width Between	1000 mm	1000 mm
Max. Lift Height	1962 mm	1962 mm
Platform Height	127 mm	127 mm
Power Supply	230V/50Hz	230V/50Hz

### ALSO AVAILABLE WITH WHEEL ALIGNMENT KIT

STF40A - 4000 KG WHEEL ALIGNMENT 4 POST HOIST



### OPTIONAL EQUIPMENT & ACCESSORIES

STJ20  
LOW PROFILE  
MANUAL JACKING  
BRIDGES

To suit:  
STF40 / STF40A



STRK01  
DRIVE-THRU RAMP KIT  
To suit:  
STF40

STRK02  
DRIVE-THRU RAMP KIT  
To suit:  
STF40A