



## SUMMIT STF635 6.35T 4 Post Hoist

### Features

- 6350 kg lift capacity
- Lift height of 2000 mm (top of platform)
- Single point operation with air operated lock release
- 18 lock positions allow runways to be level at multiple working heights
- Heavy duty high-performance cable & sheaves system
- Hydraulic cylinder under platform and out of the way
- Durable powder coat finish
- Self-chocking tilt approach ramps with non-skid coating and protective strips on ramps prevent floor gouging
- Optional STJ31 air operated jacking bridges
- Optional FC5760-14 air line kit for jacking bridges
- Optional STRK04 extra long ramp kit

## SUMMIT STF635A 6.35T 4 Post Alignment Hoist

### Features

- 6350 kg lift capacity
- Wheel alignment kit with turntable recesses & full width slip plates
- Lift height of 2051 mm (top of platform)
- Single point operation with air operated lock release
- 18 lock positions allow runways to be level at multiple working heights
- Heavy duty high-performance cable & sheaves system
- Hydraulic cylinder under platform and out of the way
- Durable powder coat finish
- Self-chocking tilt approach ramps with non-skid coating and protective strips on ramps prevent floor gouging
- Optional STJ31 air operated jacking bridges
- Optional FC5760-14 air line kit for jacking bridges
- Optional STRK04 extra long ramp kit



## SUMMIT STJ31 3.175T Air Operated Jack

### Features

- 3175 kg lift capacity
- Air operated
- Simply plug shop air line direct to jack to operate



Specifications	STF635	STF635A
Max. Lift Capacity	6350 kg	6350 kg
Overall Length	6350 mm	6350 mm
Overall Width	3570 mm	3570 mm
Overall Height	2299 mm	2299 mm
Width Between Posts	2952 mm	2952 mm
Length Between Posts	4960 mm	4960 mm
Platform Width	508 mm	508 mm
Width Between Platform	1092 mm	1092 mm
Max. Lift Height	2000 mm	2051 mm
Platform Height	210 mm	260 mm
Power Supply	415V/50Hz	415V/50Hz